

DAV PUBLIC SCHOOL
MEERACHAK, INDUSTRIAL ESTATE, BARARI, BHAGALPUR
(BIHAR)


Ph. No. 7033986840

Email: bgpdav@gmail.com, Website : www.davbhagalpur.com
(Managed by : DAV College Managing Committee, New Delhi -55)

TENDER NOTICE

Sealed quotations are invited from reputed and experienced firm as per following details.

		Particulars				
	Name of work	Repair of Boys & Girls Toilets				
	Estimate Area	(179.86 + 179.86) Sq. feet/Sq. mtr. (As Per Estimate)				
	Description of Type of Work	Repair of Boys & Girls Toilets				
SL.NO		DESCRIPTION	UNIT	QTY.	RATE	AMOUNT
1		Dismantling of flushing cistern of any size including stacking of useful materials near the site and disposal of unserviceable materials within 50 metres lead				
		Dismantling tile work in floors and roofs laid in cement mortar including stacking material within 50 metres lead.				
		For thickness of tiles 10 mm to 25 mm				
		Demolishing cement concrete including disposal of material within 50 metre lead:				
		1:3:6 or richer mix				
		Earth work in excavation over areas (exceeding 30 cm in depth. 1.5 m in width as well es 10 sqm on plan) including disposal of excavated earth , lead upto 50 m and lift upto 1.5 m; disposed earth to be levelled and neatly dressed.				
		All Kinds of soil				
		Dismantling old plaster or skirting raking out joints and cleaning the surface for plaster including disposal of rubbish to the dumping ground within 50 metres lead.				
		Disposal of building rubbish / malba / similar unserviceable, dismantled or waste materials by mechanical means, including loading, transporting, unloading to approved municipal dumping ground or as approved by Engineer-in-charge, beyond 50 m initial lead, for all leads including all lifts involved.				


Principal Cum Asstt. Regional Officer
DAV Public School
Meerachak Industrial Estate
Barari, Bhagalpur
Affiliation No. 330127

		Providing and laying water proofing treatment to vertical and horizontal surfaces of depressed portions of W.C. kitchen and the like consisting of: (i) 1st course of applying cement slurry @ 4.4 kg/sqm mixed with water proofing compound conforming to IS 2645 in recommended proportions.(ii) 11 nd course of 20 mm cement plaster 1:3 (1 cement:3 coarse sand)mixed with water proofing compound in recommended proportion, (iii) 11th course of applying blown or/residual bitumen applied hot at 1.7 kg. per sqm of area, (iv) 14th course of 400 micron thick PVC sheet.(Overlaps at joints of PVC sheet should be 100 mm wide and pasted to each other with bitumen @ 1.7 kg/sqm).				
		Supply and stacking of Fly ash conforming to IRC- 58 at site, including carriage, loading , unloading & stacking up to any lead				
		Providing and laying in position cement concrete of specified grade excluding the cost of centring and shuttering all work upto plinth level.				
		1:2:4(1 Cement: 2 coarse sand:4 graded stone aggregate 20 mm nominal size)				

		Providing and laying Ceramic glazed floor tiles 300x300 mm (thickness to be specified by the manufacturer) of 1st quality conforming to IS : 15622 of approved make in colours such as white , Ivory , Grey , Fume Red , Brown , laid on 20 mm thick Cement mortar 1:4 (1 cement: 4 coarse sand) including pointing the joints with white cement and matching pigment etc., complete.				
		Providing and fixing 1st quality ceramic glazed wall tiles conforming to IS : 15622 (Thickness to be specified by the manufacturer) of approved make in all colours, shades except burgundy , bottle green , black of any size as approved by Engineer-in-charge in skirting , risers of steps and dados over 12 mm thick bed of cement Mortar 1:3(1 cement: 3 coarse sand) and jointing with grey cement slurry @ 3.3 kg per sqm including pointing in white cement mixed with pigment of matching shade complete.				
		6 mm cement plaster to ceiling of mix :				
		1:3(1 cement: 3 coarse sand)				
		12 mm cement plaster of mix:				
		1:6(1 cement: 6 coarse sand)				
		Applying one coat of cement primer of approved brand and manufacture on wall surface:				
		Cement primer				
		Wall painting with plastic emulsion paint of approved brand and manufacture to give an even shade:				
		Two or more coats on new work				
		Providing and fixing water closet squatting pan (Indian type W.C pan) with 100mm sand cast Iron P or S trap, 10 litre low level white P.V.C flushing cistern with manually controlled device (handle lever) conforming to IS:7231, with all fittings and fixtures complete including cutting and making good the walls and floors wherever required:				
		White Vitreous china Orissa pattern W.C pan of size 580x440mm with integral type foot rests.				

		Providing and fixing white vitreous china flat back or wall corner type lipped front urinal basin of 430 x 260 x 350 mm and 340 x 410 x 265 mm sizes respectively with automatic flushing cistern with standard flush pipe and C.P. brass spreaders with brass unions G.I. clamps, complete, including painting of fittings and brackets, cutting and making good the walls and floors wherever required:				
		Range of two urinal basins with 5 litre white P.V.C. automatic flushing cistern				
		Range of three urinal basins with 10litre white P.V.C. automatic flushing cistern				
		Providing and fixing PTMT liquid soap container 109mm wide, 125mm high and 112mm distance from wall of standard shape with bracket of the same materials with snap fittings of approved quality and colour weighing not less than 105 gms.				
		Providing and fixing PTMT towel ring trapezodial shape 215mm long, 200mm wide with a minimum distances of 37mm from wall face with concealed fittings arrangement of approved quality and colour. Weighing not less than 88 gms.				
		Providing and fixing PTMT towerl rail complete with brackets fixed to wooden cleats with CP brass screws with concealed fitting arrangement of approved quality and colour.				

		450mm long towel rail with total length of 495mm, 78mm wide and effective height of 88mm, weighing not less than 170 gms.				
		Providing and fixing PVC Soil ,Waste & vent pipes all complete				
		110 mm dia				
		40 mm dia				
		Providing and fixing PVC fittings all complete as/specification & direction of E/I				
		110 mm vent cowel				
		110 mm plain bend				
		110 mm dia X 45 Bend				
		110 X 110 mm dia plain - y				
		110 X 110 mm dia plain tee				
		110 X 110 mm dia door tee				
		110 mm pipe clip				
		110 X 110 mm dia p-trap				
		40 mm elbow				
		40 mm plain tee				
		WATER SUPPLY				
		Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability for hot & cold water supply, including all CPVC plain & brass threaded fittings, including fixing the pipe with clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC solvent cement and testing of joints complete as per direction of Engineer in Charge.				

		Internal work - Exposed on wall				
		20 mm Nominal outer dia pipes				
		25 mm Nominal outer dia pipes				
		32 mm Nominal outer dia pipes				
		Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability for hot & cold water supply, including all CPVC plain & brass threaded fittings, including fixing the pipe with clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC solvent cement and testing of joints complete as per direction of Engineer in Charge.				
		Concealed work, including cutting chases and making good the				
		20 mm Nominal outer dia pipes				
		25 mm Nominal outer dia pipes				
		Providing and fixing brass stop cock of approved quality				
		20 mm Nominal bore				
		Providing and fixing gun metal gate valve with C.I. wheel of approved quality.				
		25 mm Nominal bore				
		32 mm Nominal bore				
		Providing and fixing uplasticised PVC connection pipe with brass unions.				
		45 cm length				
		15 mm Nominal bore				
		Providing and fixing G.I. union in G.I. pipe including cutting and threading the pipe and making long screws etc.				
		20 mm dia. Nominal bore				
		25 mm dia. Nominal bore				
		32 mm dia. Nominal bore				
		C.P. BRASS FITTINGS				
		Providing and fixing C.P. brass bib cock of approved quality conforming to IS :8931.				
		15 mm Nominal bore				

		Providing and fixing C.P. brass long nose bib cock of approved quality conforming to IS standards and weighing not less than 810 gms.				
		15 mm Nominal bore				
		Providing and fixing C.P. brass angle valve for basin mixer and geyser points of approved quality conforming to IS:8931				
		15 mm Nominal bore				
		Providing and fixing C.P. brass stop cock (concealed) of standard design & of approved make conforming to IS 8931.				
		15 mm Nominal bore				
		Providing and fixing C.P. brass shower rose with 15 or 20 mm inlet				

		100 mm diameter				
		Providing and fixing PTMT grating of approved quality and colour.				
		Circular type				
		100mm nominal dia.				
		Providing and fixing PTMT soap Dish Holder having length of 138mm, breadth 102mm, height of 75mm with concealed fitting arrangements. Weighing not less than 106 gms.	Sqm	179.86		
		Size:484 x 4 = 1936 S.Ft = 179.86 Sqm				
		TOTAL				
SL.NO		DESCRIPTION	UNIT	QTY.	RATE	AMOUNT
1		Dismantling of flushing cistern of any size including stacking of useful materials near the site and disposal of unserviceable materials within 50 metres lead				
		Dismantling tile work in floors and roofs laid in cement mortar including stacking material within 50 metres lead.				
		For thickness of tiles 10 mm to 25 mm				
		Demolishing cement concrete including disposal of material within 50 metre lead:				
		1:3:6 or richer mix				
		Earth work in excavation over areas (exceeding 30 cm in depth. 1.5 m in width as well es 10 sqm on plan) including disposal of excavated earth , lead upto 50 m and lift upto 1.5 m; disposed earth to be levelled and neatly dressed.				
		All Kinds of soil				
		Dismantling old plaster or skirting raking out joints and cleaning the surface for plaster including disposal of rubbish to the dumping ground within 50 metres lead.				
		Disposal of building rubbish / malba / similar unserviceable, dismantled or waste materials by mechanical means, including loading, transporting, unloading to approved municipal dumping ground or as approved by Engineer-in-charge, beyond 50 m initial lead, for all leads including all lifts involved.				
		Providing and laying water proofing treatment to vertical and horizontal surfaces of depressed portions of W.C. kitchen and the like consisting of: (i) 1st course of applying cement slurry @ 4.4 kg/sqm mixed with water proofing compound conforming to IS 2645 in recommended proportions.(ii) 11 nd course of 20 mm cement plaster 1:3 (1 cement:3 coarse sand)mixed with water proofing compound in recommended proportion, (iii) Illrd course of applying blown or/residual bitumen aplied hot at 1.7 kg. per sqm of area, (iv) Ivth course of 400 micron thick PVC sheet.(Overlaps at joints of PVC shet should be 100 mm wide and pasted to each other with bitumen @ 1.7 kg/sqni).				
		Supply and stacking of Fly ash conforming to IRC- 58 at site, including carriage, loading , unloading & stacking up to any lead				
		Providing and laying in position cement concrete of specified grade exluding the cost of centring and shuttering. all work upto plinth level.				

Principal Cum Asstt. Regional Officer

DAV Public School

Meerachak Industrial Estate

Barari, Bhagalpur

Affiliation. No.-330127

		1:2:4(1 Cement: 2 coarse sand:4 graded stone aggregate 20 mm nominal size)				
		Providing and laying Ceramic glazed floor tiles 300x300 mm (thickness to be specified by the manufacturer) of ist quality conforming to IS : 15622 of approved make in colours such as white , Ivory , Grey , Fume Red , Brown , laid on 20 mm thick Cement motar 1:4 (1 cement: 4 coarse sand) including pointing the joints with white cement and matching pigment etc., complete.				
		Providing and fixing 1st quality ceramic glazed wall tiles conforming to IS : 15622 (Thickness to be specified by the manufacture) of approved make in all colours, shades except burgundy , bottle green , black of any size as approved by Engineer-in-charge in skirting , risers of steps and dados over 12 mm thick bed of cement Motar 1:3(1 cement: 3 coarse sand) and jointing with grey cement slurry @ 3.3 kg per sqm including pointing in white cement mixed with pigment of matching shade complete.				
		6 mm cement plaster to ceiling of mix :				
		1:3(1 cement: 3 coarse sand)				
		12 mm cement plaster of mix:				
		1:6(1 cement: 6 coarse sand)				
		Applying one coat of cement primer of approved brand and manufacture on wall surface:				
		Cement primer				
		Wall painting with plastic emulsion paint of approved brand and manufacture to give an even shade:				
		Two or more coats on new work				
		Providing and fixing water closet squatting pan (Indian type W.C pan) with 100mm sand cast Iron P or S trap, 10 litre low level white P.V.C flushing cistern with manually controlled device (handle lever) conforming to IS:7231, with all fittings and fixtures complete including cutting and making good the walls and floors wherever required:				
		White Vitreous china Orissa pattern W.C pan of size 580x440mm with integral type foot rests.				
		Providing and fixing white vitreous china flat back or wall corner type lipped front urinal basin of 430 x 260 x 350 mm and 340 x 410 x 265 mm sizes respectively with automatic flushing cistern with standard flush pipe and C.P. brass spreaders with brass unions G.I. clamps, complete, including painting of fittings and brackets, cutting and making good the walls and floors wherever required:				
		Range of two urinal basins with 5 litre white P.V.C. automatic flushing cistern				
		Range of three urinal basins with 10litre white P.V.C. automatic flushing cistern				
		Providing and fixing PTMT liquid soap container 109mm wide, 125mm high and 112mm distance from wall of standard shape with bracket of the same materials with snap fittings of approved quality and colour weighing not less than 105 gms.				



		Providing and fixing PTMT towel ring trapezoidal shape 215mm long, 200mm wide with a minimum distances of 37mm from wall face with concealed fittings arrangement of approved quality and colour. Weighing not less than 88 gms.				
		Providing and fixing PTMT towerl rail complete with brackets fixed to wooden cleats with CP brass screws with concealed fitting arrangement of approved quality and colour.				

		450mm long towel rail with total length of 495mm, 78mm wide and effective height of 88mm, weighing not less than 170 gms.				
		Providing and fixing PVC Soil ,Waste & vent pipes all complete				
		110 mm dia				
		40 mm dia				
		Providing and fixing PVC fittings all complete as/specification & direction of E/I				
		110 mm vent cowel				
		110 mm plain bend				
		110 mm dia X 45 Bend				
		110 X 110 mm dia plain - y				
		110 X 110 mm dia plain tee				
		110 X 110 mm dia door tee				
		110 mm pipe clip				
		110 X 110 mm dia p-trap				
		40 mm elbow				
		40 mm plain tee				
		WATER SUPPLY				
		Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability for hot & cold water supply, including all CPVC plain & brass threaded fittings, including fixing the pipe with clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC solvent cement and testing of joints complete as per direction of Engineer in Charge.				
		Internal work - Exposed on wall				
		20 mm Nominal outer dia pipes				
		25 mm Nominal outer dia pipes				
		32 mm Nominal outer dia pipes				
		Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability for hot & cold water supply, including all CPVC plain & brass threaded fittings, including fixing the pipe with clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC solvent cement and testing of joints complete as per direction of Engineer in Charge.				
		Concealed work, including cutting chases and making good the				
		20 mm Nominal outer dia pipes				

	25 mm Nominal outer dia pipes				
	Providing and fixing brass stop cock of approved quality				
	20 mm Nominal bore				
	Providing and fixing gun metal gate valve with C.I. wheel of approved quality.				
	25 mm Nominal bore				
	32 mm Nominal bore				
	Providing and fixing uplasticised PVC connection pipe with brass unions.				
	45 cm length				
	15 mm Nominal bore				
	Providing and fixing G.I. union in G.I. pipe including cutting and threading the pipe and making long screws etc.				
	20 mm dia. Nominal bore				
	25 mm dia. Nominal bore				
	32 mm dia. Nominal bore				
	C.P. BRASS FITTINGS				
	Providing and fixing C.P. brass bib cock of approved quality conforming to IS :8931.				
	15 mm Nominal bore				

	Providing and fixing C.P. brass long nose bib cock of approved quality conforming to IS standards and weighing not less than 810 gms.				
	15 mm Nominal bore				
	Providing and fixing C.P brass angle valve for basin mixer and geyser points of approved quality conforming to IS:8931				
	15 mm Nominal bore				
	Providing and fixing C.P. brass stop cock (concealed) of standard design & of approved make conforming to IS 8931.				
	15 mm Nominal bore				
	Providing and fixing C.P. brass shower rose with 15 or 20 mm inlet				
	100 mm diameter				
	Providing and fixing PTMT grating of approved quality and colour.				
	Circular type				
	100mm nominal dia.				
	Providing and fixing PTMT soap Dish Holder having length of 138mm, breadth 102mm, height of 75mm with concealed fitting arrangements. Weighing not less than 106 gms.	Sqm	179.86		
	Size: 484 x 4 = 1936 S.Ft = 179.86 Sqm				
	TOTAL				

Principal Cum Asstt. Regional Officer


DAV Public School

Meerachak Industrial Estate

Barari, Bhagalpur

Affiliation No. 330127

	1.	Time of completion	12/06/2025
	2.	Date of Tender Notification	16/05/2025
	3.	Last date/ time for Receipt of Bids	22/05/2025
	4.	Name and address of office inviting Tender	The Principal, DAV Public School, Barari, Bhagalpur
	5.	Contact No. of procurement of Office	7033986840


 Principal Cum Asstt. Regional Officer
DAV Public School
 Meerachak Industrial Estate
 Barari, Bhagalpur
 Affiliation. No.-330127